

# FlexPay 6 Modular 15 in. (M2-15) Outdoor Payment Terminal



The M2-15 features a flush 15.6" HTML5 Full Touch Display, PCI 6.x compliance, standard contactless, and barcode scanning capabilities, ensuring secure and efficient transactions. With cloud connectivity, plug-in P2PE architecture, and customizable branding options, M2-15 helps busy retailers maximize uptime and enhance customer engagement while extending the life of their payment devices.

## Key Benefits & Features



### Intuitive User Experience

- Flush mounted 15.6" HTML5 & Full Touch Display
- Highly interactive and user-friendly interface
- Standard alphanumeric functionality for versatile data entry



### Robust Security Standards

- Engineered with PCI 6.x compliance, SRED, and latest EMV standards
- Security framework protects businesses and customers
- P2PE



### Sleek & Functional Design

- Flush mounted display
- A2-O5 compact footprint



### Maximized Uptime & Connectivity

- Leverage ICS & Forecourt (IS360) for remote monitoring and management



### Dynamic Brand Engagement Opportunities

- Engage media
- Engage prompt



## FlexPay 6 M2-15 Specifications

<b>Application Processor</b>	▪ Quad-core processor	<b>Operating Temperature (powered)</b>	▪ -30° C - +70° C
<b>Memory (RAM/Flash)</b>	▪ 2GB / 8GB	<b>Power Supply</b>	▪ 24V ± 10%
<b>Secure PIN Pad</b>	▪ PIN-on-glass	<b>Peripheral Ports</b>	▪ Ethernet
<b>Graphic Display</b>	▪ Full color, Industrial HD touchscreen - portrait ▪ Video: 30 fps		▪ External speaker connector
<b>Audio</b>	▪ Internal Speaker	▪ External Mic-in / Line-out	
<b>Card Reader</b>	▪ Separate chip (EMV) and 3 track magnetic card reader	▪ USB Host (supported drivers required)	
<b>Contactless Reader</b>	▪ Integrated – ISO14443 type A&B, MIFARE, EMV	▪ GPIO	
<b>Integrated Barcode Reader</b>	▪ Support 1D & 2D (QR) barcodes	▪ HDMI / LVDS display ports	
<b>Operating System</b>	▪ Sequoia 5.x	<b>Security</b>	▪ PCI PTS v6.x including SRED
		<b>Size</b>	▪ EMV Level 1 and 2
		<b>Printer</b>	▪ Sophisticated tamper detection
			▪ Contactless v3.x
			▪ 106 mm. (w) x 146 mm. (h) x 80.5 mm. (d)